

Approved body No. 1121

Certificate of constancy of performance 1121-CPR-UK-AC7008

In compliance with Construction Products Regulation 2011 (retained EU law EUR 2011/305) as amended by the Construction Products (Amendment etc.) (EU Exit) Regulations 2019 and the Construction Products (Amendment etc.) (EU Exit) Regulations 2020, this certificate applies to the Construction Product:

Simonswerk UK Ltd – Brass Phosphor Bronze Washered Hinges See Annex A

Intended use: For use on fire/smoke compartmentation doors, and escape route doors

Essential characteristics	Performance	Harmonised technical specification
	Mechanical test evidence: WIL 128790, 128791, 129145 Fire Test Evidence: C132467	
Self-closing Initial friction torque (door mass 40kg) Static load Load deformation	<2 Nm Passed with a displacement under load: -lateral <2 mm -vertical <4 mm and a residual displacement after unloadinglateral <0.6 mm -vertical <0.3 mm	EN 1935:2002
Overload	Passed	
Shear strength	Passed with a lateral and vertical displacement after unloading < 3 mm	
Hinges for use on fire-resistant and/or smoke-controls doors	Grade 1: suitable for use on fire/smoke resistant door assemblies	
Durability	Passed a 200,000 cycles test with a maximum wear: -lateral <0,5 mm -vertical <1 mm and with a maximum frictional torqueafter 20 cycles <3 Nm -after the completion of 200,000 cycles <3 Nm	EN 1935:2002
Families of hinges with common design features	The hinge covered by this CPR is the hinge tested	
Corrosion resistance	Grade 4: 240 hours	
Dangerous substances	Pass: the materials in the hinge do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	EN 1935:2002



Certificate of constancy of performance

1121-CPR-UK-AC7008

produced for

Simonswerk UK Ltd Burcot Works Spring Street Tipton West Midlands

and produced in the manufacturing plant

E/008

This is coded format and the information is held by the Approved Body

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1935:2002

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **03/07/2021** and will remain valid as long as neither the designated standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Approved Product Certification Body.

Valid to: 02/07/2024

UK

Paul Duggan Certification Manager

Warringtonfire Testing and Certification Limited Holmesfield Road, Warrington, Cheshire, WA1 2DS, UK



Certificate of constancy of performance 1121-CPR-UK-AC7007

Annex A

INOX Hinge Reference	Description
1440	100mm x 65mm Brass Phosphor Bronze Washered Hinges
1450	100mm x 75mm Brass Phosphor Bronze Washered Hinges
1460	100mm x 100mm Brass Phosphor Bronze Washered Hinges
1470	125mm x 75mm Brass Phosphor Bronze Washered Hinges
1480	150mm x 75mm Brass Phosphor Bronze Washered Hinges
1485	150mm x 100mm Brass Phosphor Bronze Washered Hinges
1240	100mm x 65mm Brass Phosphor Bronze Washered Hinges
1250	100mm x 75mm Brass Phosphor Bronze Washered Hinges
1260	100mm x 100mm Brass Phosphor Bronze Washered Hinges
1270	125mm x 75mm Brass Phosphor Bronze Washered Hinges
1280	150mm x 75mm Brass Phosphor Bronze Washered Hinges
1285	150mm x 100mm Brass Phosphor Bronze Washered Hinges